

200-401^{Q&As}

Managing Industrial Networks with Cisco Networking Technologies
(IMINS)

Pass Cisco 200-401 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/200-401.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers



QUESTION 1

For which three issues should fiber-optic network segments be tested? (Choose three.)

- A. attenuation
- B. near-end crosstalk
- C. length
- D. polarity
- E. jitter
- F. tensile stress

Correct Answer: ACD

QUESTION 2

According to the Purdue Reference Model, at which layer would you perform manufacturing operations and control?

- A. Level 0
- B. Level 1
- C. Level 2
- D. Level 3
- E. Level 4

Correct Answer: D

QUESTION 3

Exhibit:

```
Switch# show spanning-tree vlan 30
VLAN0030
Spanning tree enabled protocol rstp
Root ID Priority 24606
Address 00d0.047b.2800
This bridge is the root
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
Bridge ID Priority 24606 (priority 24576 sys-id-ext 30)
Address 00d0.047b.2800
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
Aging Time 300
Interface    Role    Sts    Cost    Prio.Nbr    Type
-----
Fa1/1        Desg FWD    4       128.1    p2p
Fa1/2        Desg FWD    4       128.2    p2p
Fa5/1        Desg FWD    4       128.257  p2p
```

Refer to the exhibit. The output that is shown is generated at an industrial switch. Which three statements are true? (Choose three.)

- A. All ports will be in a state of discarding, learning, or forwarding.
- B. Thirty VLANs have been configured on this switch.
- C. The bridge priority is lower than the default value for spanning tree.
- D. All interfaces that are shown are on shared media.
- E. All designated ports are in a forwarding state.
- F. This switch must be the root bridge for all VLANs on this switch.

Correct Answer: ACE

QUESTION 4

You are called upon to troubleshoot connectivity problems to a network device on a production floor. You have used ping and traceroute to verify that you cannot connect to the device from the management network. The network is 209.165.202.128/27 and the device has been given the IP address 209.165.202.158 and mask 255.255.255.224. You have verified that you can reach the device with your computer connected to the same switch as the device. What could be the cause of this problem?

- A. The device is set to the wrong subnet mask.
- B. The device is set to the wrong IP address.
- C. The device has no IP default gateway.
- D. The device is connected to a switchport in the wrong VLAN.

Correct Answer: C

QUESTION 5

Which two commands can help you to determine what image is running on your industrial switch? (Choose two.)

- A. show version
- B. show spanning-tree
- C. show interface-switch
- D. show interfaces gigabitEthernet x/y switchport
- E. show license

Correct Answer: AE

[200-401 PDF Dumps](#)

[200-401 Study Guide](#)

[200-401 Exam Questions](#)