

642-747^{Q&As}

Implementing Cisco Unified Wireless Mobility Services

Pass Cisco 642-747 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.lead4pass.com/642-747.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers



https://www.lead4pass.com/642-747.html

2021 Latest lead4pass 642-747 PDF and VCE dumps Download

QUESTION 1

When planning on tracking rogue APs, RFID tags that are based on RSSI, and wireless clients, what is needed for the Cisco 3300 Series MSE v7.0?

- A. wIPS license, context-aware license, and Cisco RFID tag license only
- B. wIPS license, context-aware license, and partner tag engine license only
- C. wIPS license and context-aware license only
- D. context-aware license only

Correct Answer: D

QUESTION 2

What is the list of Cisco 3300 Series MSE v7.0 network location service elements that can be individually enabled or disabled for device tracking and quantity limitation?

- A. Clients and Tags only
- B. Clients, Rogue APs, Interferers, and Tags only
- C. Clients, Rogue APs, Rogue Clients, Interferers, and Tags only
- D. Wired Clients, Wireless Clients, Rogue APs, Rogue Clients, Interferers, and Tags only
- E. Wired Clients, Wireless Clients, Rogue APs, Rogue Clients, Interferers, Active Tags, and Choke Point Tags

Correct Answer: D

QUESTION 3

Authentication timeout values can sometimes require changing if they are too aggressive for wireless clients. What is the default EAP timeout value in a Cisco WLC v7.0?

- A. 5 seconds
- B. 10 seconds
- C. 20 seconds
- D. 30 seconds
- E. 60 seconds

Correct Answer: D

https://www.lead4pass.com/642-747.html

2021 Latest lead4pass 642-747 PDF and VCE dumps Download

QUESTION 4

Which two statements describe Track Optimization mode for access points? (Choose two.)

- A. It improves location tracking for 2.4 and 5 GHz.
- B. It improves location tracking only for 2.4 GHz.
- C. It improves tracking for local mode APs.
- D. It improves tracking for monitor mode APs.
- E. It improves tracking for H-REAP mode APs.

Correct Answer: BD

QUESTION 5

A WLC receives a coverage hole detection alert from an AP. What two conditions must occur for the controller to dynamically mitigate the situation? (Choose two.)

- A. The AP serving the troubled client must currently have a power level 2 or lower.
- B. The client must be able to dynamically raise its power level to match the new AP power.
- C. The AP must be RF visible to additional APs on the other side of the coverage hole for calibration.
- D. The client must have WMM-PS disabled to allow for the increased power usage.
- E. The AP serving the troubled client must currently have a power level higher than 2.

Correct Answer: AB

Latest 642-747 Dumps

642-747 PDF Dumps

642-747 Study Guide

To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product!

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

https://www.lead4pass.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you. To update a previously submitted ticket:





Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © lead4pass, All Rights Reserved.