

CWNA-106^{Q&As}

Certified Wireless Network Administrator

Pass CWNP CWNA-106 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.lead4pass.com/cwna-106.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by CWNP
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

What component of the 802.11 standard allows stations to reserve access to the RF medium for a specified period of time?

- A. Short guard intervals
- B. DTIMInterval
- C. Listen Interval
- D. Probe Request frames
- E. RTS or CTS frames

Correct Answer: E

QUESTION 2

To ease user complexity, your company has implemented a single SSID for all employees. However, the network administrator needs a way to control the network resources that can be accessed by each employee based on their department. What WLAN feature would allow the network administrator to accomplish this task?

- A. SNMP
- B. VRRP
- C. RBAC
- D. IPSec
- E. WIPS
- F. WPA2

Correct Answer: C

QUESTION 3

Which one of the following channels can be used for VHT transmissions?

- A. 11
- B. 6
- C. 48
- D. 1

Correct Answer: D

QUESTION 4

When performing a site survey for a Multiple Channel Architecture (MCA) system in a multi-tenant building with five floors, what aspect should you, as the site surveyor, keep in mind?

- A. The RF interference caused by passing airplanes supporting on-board Wi-Fi should be a prime consideration.
- B. The omni-directional antennas of the access points should be oriented parallel to the floor to maximize the coverage pattern across as many floors as possible.
- C. The channel reuse pattern should be three dimensional with the RF cell extending coverage of each access point to other floors.
- D. The Fresnel Zone is completely blocked between floors so each floor is considered a separate site survey.

Correct Answer: C

QUESTION 5

A Wi-Fi Alliance interoperability certificate indicates that a device is a/b/g/n certified. It further indicates one transmit and receive spatial stream for both the 2.4 GHz and 5.0 GHz bands. It further indicates support for both WPA and WPA2 Enterprise and Personal. Finally, it indicates support for EAP-TLS, EAP-TTLS/MSCHAPv2, PEAPv0/EAP-MSCHAPv2 and PEAPv1/EAP-GTC. Which one of the following statements is false?

- A. This client device supports protection mechanisms such as RTS/CTS and/or CTS-to-Self.
- B. This client device supports both TKIP and CCMP ciphersuites.
- C. 300 Mbps is the maximum supported data rate for this device.
- D. This client device supports X.509 certificates for EAP authentication.

Correct Answer: C

[CWNA-106 VCE Dumps](#)

[CWNA-106 Practice Test](#)

[CWNA-106 Braindumps](#)