

HC-711-ENU^{Q&As}

HCNA Huawei Certified Network Associate - Constructing Basic Security Network (HCNA-CBSN) - ENU





Pass Huawei HC-711-ENU Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/hc-711-enu.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

About the VLAN tag processing, the following description of the error is?

- A. When Trunk port receives a frame,if the frame does not contain 802.1Q tag header, will be marked with PVID port; If the frame contains the 802.1Q tag header, no change.
- B. When Trunk port to send the frame,when the port's PVID VLAN ID of the frame is not the same,discarded; When PVID VLAN ID and port with the same time frame,the pass-through
- C. When Access port receives a frame,if the frame does not contain 802.1Q tag header, will be marked with PVID port; If the frame contains the 802.1Q tag header, the switch does not deal with them directly discarded.
- D. When Access port to send frames,stripping 802.1Q tag header, frame issued ordinary Ethernet frames

Correct Answer: B

QUESTION 2

When a router receives a packet, if no match is found, the specific route entry, the default routing table can be forwarded.

- A. True
- B. False

Correct Answer: A

QUESTION 3

About SVN3000 hardware description, is correct: (Choose three)

- A. SVN3000 a 1U standard chassis,the chassis with Console port
- B. There are four pairs SVN3000 fixed 10/100/1000M Ethernet optical ports are mutually exclusive
- C. Provided a total of two expansion slots on the chassis,one for encryption card is inserted,another spare for extended functions.
- D. SVN3000 installed two internal AC or DC power modules, redundant dual power supply and backup power supply.

Correct Answer: ACD

QUESTION 4

IP-Link auto- detection results can only be applied to detect double hot backup.

- A. True

B. False

Correct Answer: B

QUESTION 5

Which of the following stages of the second stage belongs to IKE exchange mode?

A. Master Mode

B. Aggressive Mode

C. Fast mode

D. Passive mode

Correct Answer: C

[Latest HC-711-ENU Dumps](#)

[HC-711-ENU Practice Test](#)

[HC-711-ENU Study Guide](#)