299-01 ^{Q&As}

Riverbed Certified Solutions Professional - Network Performance Management

Pass Riverbed 299-01 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.leads4pass.com/299-01.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Riverbed Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

If Cascade is unable to keep a record of all hops traversed due to exceeding its limits, what is the order of preference for selecting which hops to preserve?

A. Preserve order as received at Gateway.

B. Preserve order as received at Profiler.

C. Sensors, Sensor-VEs, Steelheads, xFlow (NetFlow, sFlow, Jflow, Cflow...).

D. Steelheads, Sensors, Sensor-VEs, xFlow (NetFlow, sFlow, Jflow, Cflow...).

E. xFlow (NetFlow, sFlow, Jflow, Cflow...), Steelheads, Sensors, Sensor-VEs.

Correct Answer: D

QUESTION 2

When the Discovery wizard presents all newly discovered application-ports as candidates to be included as segments for monitoring within a Service, which of the following actions will save the segment as part of the Service, but will not implement monitoring of the traffic? This action will also suppress the same application-ports from being presented in any future discovery.

A. Merge

B. Add

C. Drop

D. Delete

E. Discover

Correct Answer: C

QUESTION 3

When changing the priority for a Layer 4 mapping on Cascade Profiler best practices indicate that Application Mappings should be given higher priorities based on:

A. Longest Match

B. Shortest Match

C. IP and Port

D. IP

Correct Answer: A

QUESTION 4

When editing a previously configured service policy, what options become available if you click the \\'show advanced settings\\' checkbox? (Select 3)

A. Allows enabling/disabling the detection of dips in the metric.

B. Allows tuning of the tolerance range of the metric.

C. Allows setting of a noise floor for the metric.

D. Allows adjusting the notifications for the metric.

E. Allows enabling/disabling the detection of spikes in the metric.

Correct Answer: ACE

QUESTION 5

Which of the following is valid syntax for defining host groups? (Select 3)

A. 192.168.0.100/255.255.0.255 Philadelphia

B. 192/8 Baltimore

C. 172.168.1.1 Phoenix

D. 10/16 Chicago

Correct Answer: ABC

[299-01 PDF Dumps](link)   [299-01 VCE Dumps](link)   [299-01 Study Guide](link)