

642-813^{Q&As}

Implementing Cisco IP Switched Networks

Pass Cisco 642-813 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.lead4pass.com/642-813.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers



VCE & PDF Lead4Pass.com

https://www.lead4pass.com/642-813.html

2021 Latest lead4pass 642-813 PDF and VCE dumps Download

QUESTION 1

After port security is deployed throughout an enterprise campus, the network team has been overwhelmed with port reset requests. They decide to configure the network to automate the process of re-enabling user ports. Which command accomplishes this task?

- A. switch(config)# errdisable recovery interval 180
- B. switch(config)# errdisable recovery cause psecure-violation
- C. switch(config)# switchport port-security protect
- D. switch(config)# switchport port-security aging type inactivity
- E. switch(config)# errdisable recovery cause security-violation

Correct Answer: B

QUESTION 2

What is the maximum number of 10 Gigabit Ethernet connections that can be utilized in an EtherChannel for the virtual switch link?

- A. 4
- B. 6
- C. 8
- D. 12

Correct Answer: C

QUESTION 3

When a Layer 2 EtherChannel is configured, which statement about placement of the IP address is true?

- A. The IP address is placed on the highest numbered member port.
- B. The IP address is placed on the port-channel logical interface.
- C. The IP address is placed on the lowest numbered member port.
- D. The IP address is assigned via DHCP only.

Correct Answer: B

https://www.lead4pass.com/642-813.html

2021 Latest lead4pass 642-813 PDF and VCE dumps Download

QUESTION 4

Which four LACP components are used to determine which hot-standby links become active after an interface failure within an EtherChannel bundle? (Choose four.)

- A. LACP system priority
- B. LACP port priority
- C. interface MAC address
- D. system ID
- E. port number
- F. hot-standby link identification number
- G. interface bandwidth

Correct Answer: ABDE

QUESTION 5

While working in the core network building, a technician accidently bumps the fiber connection between two core switches and damages one of the pairs of fiber. As designed, the link was placed into a non-forwarding state due to a fault with UDLD. After the damaged cable was replaced, the link did not recover. What solution allows the network switch to automatically recover from such an issue?

- A. macros
- B. errdisable autorecovery
- C. IP Event Dampening
- D. command aliases
- E. Bidirectional Forwarding Detection

Correct Answer: B

642-813 Practice Test

642-813 Study Guide

642-813 Braindumps



To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product!

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

https://www.lead4pass.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you. To update a previously submitted ticket:





Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © lead4pass, All Rights Reserved.