

H12-891^{Q&As}

HCIE-Datacom V1.0

Pass Huawei H12-891 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/h12-891.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

ISIS elects DIS in broadcast multiplexed access networks, and the following statement about DIS is correct?(Multiple choice)

- A. ISIS elects dis by comparing priorities, and mac addresses if the priorities are consistent
- B. In a broadcast multiple access network, DIS sends Hello PDUs at three times the frequency
- C. DIS guarantees database synchronization by periodically sending CSNP messages
- D. DIS supports preemption function, after the new DIS preemption is successful, there is no need to flood any LSP packet

Correct Answer: ABC

QUESTION 2

IPV6 multicast introduces the concept of multicast scope, which of the following ways is the multicast scope concept implemented? Multi-select

- A. When the group shake source sends IP6 multicast data, the TTL value of the packet is set to limit the transmission range of the group shake
- B. There is a special field in the IPv6 multicast address that specifies the propagation range of multicast.
- C. Multicast scope is just a concept of spreading scope, and there is no specific technical implementation.
- D. During network configuration, the administrator uses the configuration command at the edge of the network to limit the multicast scope.

Correct Answer: BD

QUESTION 3

In the use of the LACP protocol, the following description is correct ?(Multiple select).

- A. You can avoid the Eth-Trunk interface from frequently shaking interface eth-trunk 1l lacp preempt enable lacp preempt delay delay-time with the following command
- B. Source IP address load sharing, interface eth-trunk1Load-balance src-dst-ip, can be configured in an enabled link aggregation group with the following command
- C. The member interface can be removed from an enabled link aggregation group with the following command: interface GigabitEthernet0/0/1 Shutdown nterface Gigabithemet/O/1undo eth-trunklinterface GigabitEthemet0/0/1 undo shutdown
- D. A chain cluster that can be initiated through an order Join the member interface :interface GigabitEthemeto/0/1 shutdown interface igabitEthemetO/0/1 tunkportGigabitEthermet0/0/1 interface GigabitEthermet0/0/1 Undo shutdown

Correct Answer: AC

QUESTION 4

In Huawei switches, the hybrid port can select vlan1 as an untagged vlan

- A. True
- B. False

Correct Answer: A

QUESTION 5

If multiple candidate RPs are configured in a multicast group, which of the following parameters does the RP that elect the group from multiple candidate RPs need to be compared?

- A. The mask length of the group range for the C-RP service that matches the group address that the user joined
- B. C-RP priority
- C. The IP address of the C. C-RP interface Number of
- D. C-RP interface

Correct Answer: ABC

[H12-891 Study Guide](#)

[H12-891 Exam Questions](#)

[H12-891 Braindumps](#)