

HCE-5420^{Q&As}

Hitachi Data Systems Certified Specialist - Content Platform

Pass Hitachi HCE-5420 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/hce-5420.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Hitachi
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

A customer ordered a HCP 500 DL system. One of the nodes must be replaced. The HBA is in its original configuration.

Which three actions should you perform? (Choose three.)

- A. Configure the HBA to boot from LUN100 of the connected Hitachi storage system.
- B. Reload the HBA firmware.
- C. Enable the HBA BIOS.
- D. Set the HBA topology to point-to-point.
- E. Set the boot sequence to a USB boot device.

Correct Answer: BCD

QUESTION 2

You are implementing encryption in a new HCP installation and the customer has asked about the overall performance impact resulting from the use of the encryption feature. What is the impact when compared to a similar unencrypted solution?

- A. It is not measurable.
- B. It is 10% to 20%.
- C. It is 40% to 50%.
- D. It is less than 10%.

Correct Answer: B

QUESTION 3

During installation, you configured the NTP option as internal. Post installation, the customer instructs you to configure the NTP option with external servers. The HCP internal clock is currently more than 20 minutes out of sync with the current time. What will happen when you configure NTP with external servers?

- A. The next time the HCP is restarted, the current time will be changed.
- B. The current time will be set then HCP will restart.
- C. The current time will be set and HCP will not restart.
- D. Any search nodes in the HCP will re-index all their data;

Correct Answer: B

QUESTION 4

Your customer wants to use IP addresses which conflict with the default HCP network settings. As a result you need to change the back-end IP addresses for each HCP node. Which HCP network settings should you change?

- A. the back-end gateway router IP address
- B. the back-end subnet mask
- C. the first three octets of the back-end IP addresses
- D. the fourth octet of the back-end IP addresses

Correct Answer: C

QUESTION 5

When performing HCP maintenance using PuTTY, what is used to forward the SSH keys?

- A. Pageant
- B. Pelican
- C. Polaris
- D. Proxy server

Correct Answer: A

[HCE-5420 Study Guide](#)

[HCE-5420 Exam Questions](#)

[HCE-5420 Braindumps](#)