

HP0-Y52^{Q&As}

Applying HP FlexNetwork Fundamentals

Pass HP HP0-Y52 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/hp0-y52.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Refer to the exhibit.

```
<Switch> display port trunk
Interface                PVID    VLAN passing
GE1/0/19                 1       1,11
```

The network administrator has configured this port to permit all VLANs. The output in the exhibit indicates that the port is only passing VLANs 1 and 11. The administrator wants the port to pass VLAN 12 as well. What should the administrator do to accomplish this?

- A. Enable IP routing.
- B. Add VLAN 12 to the switch.
- C. Change the port link-type to hybrid.
- D. Change the port link-type to access.

Correct Answer: A

QUESTION 2

When adding a new member to an existing IRF domain, which of the following must you perform first?

- A. Define the IRF priority.
- B. Create the IRF logical port.
- C. Define the IRF domain name.
- D. Define the IRF member number.

Correct Answer: D

QUESTION 3

A network administrator enters this command on an HP Comware switch:

```
save
```

In interactive mode, the administrator is prompted to save to a file named config.cfg and confirms the save. What is the effect of these actions?

- A. The current configuration is saved to config.cfg on a TFTP server but is not used for the startup-config.

- B. The startup-config, rather than the correct configuration, is saved to config.cfg on a TFTP server.
- C. The current configuration is saved to config.cfg in the flash but is not used for the startup-config.
- D. The current configuration is saved to config.cfg in the flash and is used for the startup- config.

Correct Answer: D

QUESTION 4

A company needs a two-member Intelligent Resilient Framework (IRF) virtual switch. The network administrator is configuring IRF member 2 that will connect to port 1/1 on IRF member 1. What is the correct IRF port ID for member 2?

- A. 1/2
- B. 2/2
- C. 1/1
- D. 2/1

Correct Answer: B

QUESTION 5

A network administrator plans to execute show commands as well as make configuration changes. Which HP ProVision privilege role must be assigned to an account for the administrator to do this?

- A. Operator
- B. Administrator
- C. Superuser
- D. Manager

Correct Answer: D

[Latest HP0-Y52 Dumps](#)

[HP0-Y52 Practice Test](#)

[HP0-Y52 Exam Questions](#)