

## NS0-504<sup>Q&As</sup>

NetApp Certified Implementation Engineer - SAN, Cluster-Mode

### Pass Network Appliance NS0-504 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/ns0-504.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Network Appliance Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



## QUESTION 1

What are the steps required to set the Domain ID on a Brocade switch? Choose one: A. cfgswitch : switchenable

B. switchshow : cfgshow : switchenable

C. configure : reboot

D. switchdisable : configure : switchenable

E. configure : switchshow : reboot

F. switchdisable : configure : reset

Correct Answer: D

---

## QUESTION 2

Which three are pre-requisites for using SnapRestore? (Choose three.)

A. The volume to be reverted must be offline.

B. The volume to be reverted must not be a SnapMirror destination.

C. You must enter the SnapRestore license code before you can use it.

D. Snapshot copies must exist on the storage system so that you can select a snapshot for the reversion.

Correct Answer: BCD

---

## QUESTION 3

What is NetApp's recommended best practice for zone configuration?

A. All zones should contain a single initiator and all the targets that initiator accesses.

B. Individual zones can get too complicated. It is better to simply configure one default zone with all devices contained in it.

C. All devices from the same vendor should be in one zone.

D. All zones should contain a single target and all the initiators using that target.

Correct Answer: A

---

## QUESTION 4

When verifying a customer's environment, which components should you document?

- A. host CPU speed, memory, bus slots, FC switch ports used and unused
- B. host bus slots, HBA's, FC switch ports used and unused
- C. host bus slots, HBA's, memory, FC switch ports used and unused, USB connections
- D. host CPU speed, HBA's, memory, FC switch ports used and unused

Correct Answer: A

---

## QUESTION 5

In the cabinet diagram shown, what additional information should be included to make it more complete?

- A. storage controller rack placement
- B. storage port connectivity
- C. switch connectivity
- D. storage shelf connectivity

Correct Answer: D

[NS0-504 VCE Dumps](#)

[NS0-504 Exam Questions](#)

[NS0-504 Braindumps](#)