

HCE-5710^{Q&As}

Architecting Hitachi Data Systems Certified Expert - Replication solutions

Pass Hitachi HCE-5710 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.leads4pass.com/hce-5710.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Hitachi Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

One CCI instance fails to start. You decide to review the HORCM logs to determine what is wrong. Where are the logs stored?

- A. Under /var/adm.
- B. On the Command Device.
- C. Always under Horcm/log/curlog.
- D. It depends on the environment variable.

Correct Answer: D

QUESTION 2

You have been asked to install HiCommand Protection Manager (HPtM) software in an environment where integration with backup software is required. Which three must be in place before you begin the installation? (Choose three.)

- A. RAID Manager CCI
- B. Netbackup MS SQL server agent
- C. Netbackup or Backup Exec software
- D. HiCommand Device Manager software
- E. ShadowImage software or Copy-on-Write Snapshot software

Correct Answer: ACE

QUESTION 3

Which two statements describe HiCommand Tiered Storage Manager? (Choose two.)

- A. Tiered Storage Manager can migrate data within subsystems.
- B. Tiered Storage Manager can migrate data between external subsystems.
- C. Tiered Storage Manager can migrate data only between external subsystems.
- D. Tiered Storage Manager can migrate data only between a subsystem and an external subsystem.

Correct Answer: AB

QUESTION 4

Your customer must establish a Three Data Center (3DC) Business Continuity Solution using Universal Storage

Platform (USP) systems. Which three tasks are required to setup the solution? (Choose three.)

- A. Enable bi-directional paths between local and distant USPs.
- B. Upgrade the shared memory size of the local and distant USPs.
- C. Upgrade the shared memory size on all three USPs by 25 percent.
- D. Enable bi-directional Fibre Channel links between the primary and local USPs.
- E. Implement Journal Groups of equal size and performance on local and distant USPs.

Correct Answer: ADE

QUESTION 5

During a Copy-on-Write SnapShot (CoW) implementation, a customer asks you to demonstrate the Quick Restore functionality of the software. CCI for this environment is installed on a UNIX host using korn shell and the CoW CCI device group is COW_db01. Which statement is correct?

- A. This is not possible using Copy-on-Write SnapShot.
- B. Use the pairresync -g COW_db01 -fq normal -restore commands.
- C. Use the export HORCC_REST=NORMAL; pairresync -g COW_db01 -restore commands.
- D. Use the export HORCC_REST=COW_QUICK; pairresync -g COW_db01 -restore commands.

Correct Answer: A

QUESTION 6

A paircreate command fails with the unrecoverable error code: EX_ENXCTG. Which two actions must be performed first? (Choose two.)

- A. Verify the CCI command log.
- B. Retry the paircreate command.
- C. Verify the meaning of EX_ENXCTG in the CCI manuals.
- D. Verify that the HORCM instance number being used is correct.

Correct Answer: AC

QUESTION 7

When performing a migration using Volume Migrator, which three LDEVs cannot be migrated? (Choose three.)

- A. An expanded LU volume.

- B. Volumes being used by Concurrent Copy.
- C. Volumes for which there is a pinned track.
- D. A TrueCopy source volume which is in PSUE state.
- E. Volumes being managed by Cache Residency Manager.

Correct Answer: BCE

QUESTION 8

A customer would like a scripted solution to resynchronize USP600 ShadowImage volumes and be able to access the secondary volumes within minutes while the copy is taking place in the background. The customer is running the latest CCI version on a Solaris server using the korn shell; the CCI device group name for the ShadowImage volumes is SI_db01. Which series of commands should be scripted to accomplish this?

- A. pairresync -g SI_db01 -fq pairevtwait -g SI_db01 -ss pair -t 180 pairsplit -g SI_db01 -fq
- B. pairresync -g SI_db01 -fq pairevtwait -g SI_db01 -ss pair -nowait pairsplit -g SI_db01 -fq
- C. pairresync -g SI_db01 -fq quick pairevtwait -g SI_db01 -ss pair -t 180 pairsplit -g SI_db01 -fq quick
- D. pairresync -g SI_db01 -fq normal pairevtwait -g SI_db01 -ss pair -nowait pairsplit -g SI_db01 -fq normal

Correct Answer: C

QUESTION 9

A customer would like to view the pool usage for a Copy-on-Write SnapShot (CoW) environment using CCI.

Which CCI command should the customer use?

- A.
inqraid -p pid
- B.
raidscan -p pid
- C.
pairdisplay -p pid
- D.
raidvchkscan -v pid

Correct Answer: D

QUESTION 10

You have been asked to install HiCommand Protection Manager (HPtM) software in an environment where integration with backup software is required. Which three must be in place before you begin the installation? (Choose three.)

- A. RAID Manager CCI
- B. Netbackup MS SQL server agent
- C. Netbackup or Backup Exec software
- D. HiCommand Device Manager software
- E. ShadowImage software or Copy-on-Write Snapshot software

Correct Answer: ACE

QUESTION 11

On the Storage Navigator frame for a TrueCopy pair operation, the "Status" column indicates PDUB. What is the status of the pairs indicating PDUB?

- A. This is a TrueCopy LUSE status of a pair suspended error.
- B. This status indicates that the TrueCopy pair is in the initial copy.
- C. One or more LDEV pairs are SMPL on a TrueCopy LUSE volume.
- D. The status of the TrueCopy software LUSE volume is in the initial copy.

Correct Answer: C

QUESTION 12

An Hitachi Data Systems customer is implementing a TrueCopy Extended Distance solution on an Adaptable Modular Storage (AMS) system. Which configuration is supported?

- A. TrueCopy Extended Distance with 20 Consistency Groups.
- B. TrueCopy Extended Distance Consistency Group pairs in parallel to TrueCopy Synchronous pairs.
- C. TrueCopy Extended Distance Consistency Group with a ShadowImage copy taken from the SVOL.
- D. Two or more TrueCopy Extended Distance Consistency Groups defined with opposite copy direction.

Correct Answer: D

QUESTION 13

The Command Control Interface (CCI) for the Universal Replicator pair operation displays a PFUS split type. Which three statements are true? (Choose three.)

- A. The PFUL status is displayed as PAIR status by Storage Navigator.
- B. The PFUS status is displayed as PSUS status by Storage Navigator.
- C. The pair status will change from PFUS to PSUE when the primary Journal Group is full.
- D. The pair status changes from PFUL to PFUS when the primary Journal Group is 80 percent full.
- E. The pair status will change from PFUL to PFUS when the "data overflow watch" time period is exceeded.

Correct Answer: ABE

QUESTION 14

When integrating NetBackup with HiCommand Protection Manager (HPtM), which option should you specify on the setup GUI Command Control Interface (CCI) Linkage tab?

- A. instance number
- B. CCI installation path
- C. track size for data copy
- D. dynamic reconfiguration of secondary volume

Correct Answer: B

QUESTION 15

You are using HiCommand Protection Manager (HPtM) Volume Shadow Copy Service (VSS) backup for Microsoft Exchange Server 2003. Which two statements are correct for a true online backup? (Choose two.)

- A. No need for separate VSS import servers.
- B. VSS guarantees the consistency of the data;
- C. Dismounting and other processes are no longer required.
- D. VSS import server has to be installed on the application server.

Correct Answer: BC